PRO ADJUSTABLE NOZZLES

Hunter®

Adjustable Arc Nozzles Performance Data

Arc	Pressure PSI	4 Foot Radius Adjustable from 0° to 360° Trajectory: 0° Color Code: Lt. Blue Nozzle 4A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲	6 Foot Radius Adjustable from 0° to 360° Trajectory: 0° Color Code: Lt. Green Nozzle 6A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲	8 Foot Radius Adjustable from 0° to 360° Trajectory: 0° Color Code: Brown Nozzle 8A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲
45°	20	3'	0.11	5.44	6.28	5'	0.15	3.21	3.70	7'	0.12	1.83	2.11
	25	3'	0.13	6.02	6.95	5'	0.15	3.21	3.70	8'	0.13	1.58	1.83
	30	**4'**	**0.13**	**6.45**	7.45	**6'**	**0.18**	**3.85**	**4.45**	**8'**	**0.15**	**1.75**	**2.02**
	35	4'	0.14	6.74	7.78	6'	0.18	3.85	4.45	9'	0.16	1.51	1.74
	40	4'	0.16	7.70	8.89	6'	0.19	4.06	4.69	9'	0.17	1.62	1.87
90°	20	3'	0.19	4.57	5.28	5'	0.30	3.21	3.70	7'	0.23	1.83	2.11
	25	3'	0.20	4.81	5.56	5'	0.31	3.32	3.83	8'	0.26	1.58	1.83
	30	**4'**	**0.28**	**6.74**	**7.78**	**6'**	**0.37**	**3.96**	**4.57**	**8'**	**0.29**	**1.75**	**2.02**
	35	4'	0.24	5.78	6.67	6'	0.38	4.06	4.69	9'	0.32	1.51	1.74
	40	4'	0.25	5.90	6.81	6'	0.40	4.28	4.94	9'	0.34	1.62	1.87
120°	20	3'	0.28	5.05	5.84	5'	0.37	2.97	3.43	7'	0.31	1.83	2.11
	25	3'	0.30	5.32	6.15	5'	0.38	3.05	3.52	8'	0.35	1.58	1.83
	30	**4'**	**0.34**	**6.14**	**7.09**	**6'**	**0.44**	**3.53**	**4.08**	**8'**	**0.39**	**1.75**	**2.02**
	35	4'	0.34	6.14	7.09	6'	0.46	3.69	4.26	9'	0.42	1.51	1.74
	40	4'	0.37	6.68	7.71	6'	0.48	3.85	4.45	9'	0.45	1.62	1.87
180°	20	3'	0.34	4.09	4.72	5'	0.50	2.67	3.09	7'	0.47	1.83	2.11
	25	3'	0.38	4.57	5.28	5'	0.54	2.89	3.33	8'	0.53	1.58	1.83
	30	**4'**	**0.45**	**5.41**	**6.25**	**6'**	**0.60**	**3.21**	**3.70**	**8'**	**0.58**	**1.75**	**2.02**
	35	4'	0.46	5.53	6.39	6'	0.64	3.42	3.95	9'	0.63	1.51	1.74
	40	4'	0.48	5.78	6.67	6'	0.68	3.64	4.20	9'	0.68	1.62	1.87
240°	20	3'	0.58	5.23	6.04	5'	0.73	2.93	0.85	7'	0.62	1.83	2.11
	25	3'	0.62	5.59	6.46	5'	0.78	3.13	0.90	8'	0.70	1.58	1.83
	30	**4'**	**0.68**	**6.13**	**7.08**	**6'**	**0.88**	**3.53**	**1.02**	**8'**	**0.78**	**1.75**	**2.02**
	35	4'	0.74	6.68	7.71	6'	0.92	3.69	1.07	9'	0.84	1.51	1.74
	40	4'	0.80	7.22	8.34	6'	1.02	4.09	1.18	9'	0.91	1.62	1.87
270°	20	3'	0.59	4.73	5.46	5'	0.88	3.14	3.62	7'	0.70	1.83	2.11
	25	3'	0.66	5.29	6.11	5'	0.98	3.49	4.03	8'	0.79	1.58	1.83
	30	**4'**	**0.73**	**5.86**	**6.76**	**6'**	**1.10**	**3.92**	**4.53**	**8'**	**0.87**	**1.75**	**2.02**
	35	4'	0.76	6.10	7.04	6'	1.15	4.10	4.73	9'	0.95	1.51	1.74
	40	4'	0.80	6.42	7.41	6'	1.20	4.28	4.94	9'	1.02	1.62	1.87
360°	20	3'	0.66	3.97	4.58	5'	1.05	2.81	3.24	7'	0.93	1.83	2.11
	25	3'	0.72	4.33	5.00	5'	1.10	2.94	3.40	8'	1.05	1.58	1.83
	30	**4'**	**0.80**	**4.81**	**5.56**	**6'**	**1.26**	**3.37**	**3.89**	**8'**	**1.16**	**1.75**	**2.02**
	35	4'	0.86	5.17	5.97	6'	1.30	3.48	4.01	9'	1.27	1.51	1.74
	40	4'	0.90	5.41	6.25	6'	1.40	3.74	4.32	9'	1.36	1.62	1.87

Cover all the angles. Fine-tune nozzles to the arc you need. Hey, we're on a roll. Introducing another new product from Hunter. Our new generation Pro Adjustable Nozzles are made to cover all angles. Whether hillside topography, a curved flower bed or other special landscape installation, challenging angles demand nozzles that adjust to their surroundings. Don't forget, these are perfect for right out-of-the-box standard angles as well. They offer the finest results of any adjustable arc nozzles in the industry.

We're talking well-defined, crisp edges. Engineered to deliver larger water drops, these nozzles also deter winds from dispersing water. With their matched precipitation, you can group them together, even with different radii. And their new top makes them easier to adjust than ever. Set our nozzles at any angle from 0° to 360°. You just grab a bag and go. Accomplish more with less inventory. No tools required. That's not all. They're color-coded for easy inventory and field ID. And very well-adjusted.

Arc	Pressure PSI	10 Foot Radius Adjustable from 0° to 360° Trajectory: 15° Color Code: Red Nozzle 10A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲	12 Foot Radius Adjustable from 0° to 360° Trajectory: 28° Color Code: Green Nozzle 12A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲	15 Foot Radius Adjustable from 0° to 360° Trajectory: 28° Color Code: Black Nozzle 15A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲	17 Foot Radius Adjustable from 0° to 360° Trajectory: 28° Color Code: Gray Nozzle 17A Radius ft.	Flow GPM	Precip in/hr ■	Precip in/hr ▲
45°	20	9'	0.20	1.86	2.15	11'	0.25	1.60	1.85	14'	0.37	1.46	1.69	16'	0.48	1.44	1.67
	25	10'	0.22	1.71	1.97	12'	0.28	1.52	1.76	15'	0.42	1.44	1.66	17'	0.54	1.45	1.67
	30	**10'**	**0.25**	**1.89**	**2.18**	**12'**	**0.32**	**1.68**	**1.95**	**15'**	**0.47**	**1.59**	**1.84**	**17'**	**0.60**	**1.60**	**1.85**
	35	11'	0.27	1.70	1.96	13'	0.34	1.56	1.80	16'	0.51	1.52	1.76	18'	0.65	1.55	1.79
	40	11'	0.29	1.83	2.11	13'	0.37	1.68	1.94	17'	0.54	1.45	1.68	19'	0.70	1.50	1.73
90°	20	9'	0.39	1.86	2.15	11'	0.50	1.60	1.85	14'	0.74	1.46	1.69	16'	0.96	1.44	1.67
	25	10'	0.44	1.71	1.97	12'	0.57	1.52	1.76	15'	0.84	1.44	1.66	17'	1.09	1.45	1.67
	30	**10'**	**0.49**	**1.89**	**2.18**	**12'**	**0.63**	**1.68**	**1.95**	**15'**	**0.93**	**1.59**	**1.84**	**17'**	**1.20**	**1.60**	**1.85**
	35	11'	0.53	1.70	1.96	13'	0.69	1.56	1.80	16'	1.01	1.52	1.76	18'	1.31	1.55	1.79
	40	11'	0.57	1.83	2.11	13'	0.74	1.68	1.94	17'	1.09	1.45	1.68	19'	1.41	1.50	1.73
120°	20	9'	0.52	1.86	2.15	11'	0.67	1.60	1.85	14'	0.99	1.46	1.69	16'	1.28	1.44	1.67
	25	10'	0.59	1.71	1.97	12'	0.76	1.52	1.76	15'	1.12	1.44	1.66	17'	1.45	1.45	1.67
	30	**10'**	**0.65**	**1.89**	**2.18**	**12'**	**0.84**	**1.68**	**1.95**	**15'**	**1.24**	**1.59**	**1.84**	**17'**	**1.60**	**1.60**	**1.85**
	35	11'	0.71	1.70	1.96	13'	0.91	1.56	1.80	16'	1.35	1.52	1.76	18'	1.74	1.55	1.79
	40	11'	0.77	1.83	2.11	13'	0.98	1.68	1.94	17'	1.45	1.45	1.68	19'	1.87	1.50	1.73
180°	20	9'	0.78	1.86	2.15	11'	1.01	1.60	1.85	14'	1.49	1.46	1.69	16'	1.92	1.44	1.67
	25	10'	0.89	1.71	1.97	12'	1.14	1.52	1.76	15'	1.68	1.44	1.66	17'	2.17	1.45	1.67
	30	**10'**	**0.98**	**1.89**	**2.18**	**12'**	**1.26**	**1.68**	**1.95**	**15'**	**1.86**	**1.59**	**1.84**	**17'**	**2.40**	**1.60**	**1.85**
	35	11'	1.07	1.70	1.96	13'	1.37	1.56	1.80	16'	2.02	1.52	1.76	18'	2.61	1.55	1.79
	40	11'	1.15	1.83	2.11	13'	1.48	1.68	1.94	17'	2.18	1.45	1.68	19'	2.81	1.50	1.73
240°	20	9'	1.05	1.86	2.15	11'	1.34	1.60	1.85	14'	1.98	1.46	1.69	16'	2.56	1.44	1.67
	25	10'	1.18	1.71	1.97	12'	1.52	1.52	1.76	15'	2.24	1.44	1.66	17'	2.89	1.45	1.67
	30	**10'**	**1.31**	**1.89**	**2.18**	**12'**	**1.68**	**1.68**	**1.95**	**15'**	**2.48**	**1.59**	**1.84**	**17'**	**3.20**	**1.60**	**1.85**
	35	11'	1.42	1.70	1.96	13'	1.83	1.56	1.80	16'	2.70	1.52	1.76	18'	3.48	1.55	1.79
	40	11'	1.53	1.83	2.11	13'	1.97	1.68	1.94	17'	2.91	1.45	1.68	19'	3.75	1.50	1.73
270°	20	9'	1.18	1.86	2.15	11'	1.51	1.60	1.85	14'	2.23	1.46	1.69	16'	2.88	1.44	1.67
	25	10'	1.33	1.71	1.97	12'	1.71	1.52	1.76	15'	2.52	1.44	1.66	17'	3.26	1.45	1.67
	30	**10'**	**1.47**	**1.89**	**2.18**	**12'**	**1.89**	**1.68**	**1.95**	**15'**	**2.79**	**1.59**	**1.84**	**17'**	**3.60**	**1.60**	**1.85**
	35	11'	1.60	1.70	1.96	13'	2.06	1.56	1.80	16'	3.04	1.52	1.76	18'	3.92	1.55	1.79
	40	11'	1.72	1.83	2.11	13'	2.21	1.68	1.94	17'	3.27	1.45	1.68	19'	4.22	1.50	1.73
360°	20	9'	1.57	1.86	2.15	11'	2.02	1.60	1.85	14'	2.98	1.46	1.69	16'	3.84	1.44	1.67
	25	10'	1.77	1.71	1.97	12'	2.28	1.52	1.76	15'	3.37	1.44	1.66	17'	4.34	1.45	1.67
	30	**10'**	**1.96**	**1.89**	**2.18**	**12'**	**2.52**	**1.68**	**1.95**	**15'**	**3.72**	**1.59**	**1.84**	**17'**	**4.80**	**1.60**	**1.85**
	35	11'	2.13	1.70	1.96	13'	2.74	1.56	1.80	16'	4.05	1.52	1.76	18'	5.22	1.55	1.79
	40	11'	2.30	1.83	2.11	13'	2.95	1.68	1.94	17'	4.36	1.45	1.68	19'	5.62	1.50	1.73

- **Easy grip adjustment**
- **Crisp, well defined edges**
- **Large water droplets**
- **Superior distribution pattern**
- **Matched precip rate from 8'–17'**

Hunter® THE IRRIGATION INNOVATORS

Hunter Industries Incorporated
1940 Diamond Street, San Marcos, California 92078
www.hunterindustries.com