

Angle Hose Valves

INSIST^{ON} FPPI[®]

UL, ULC and FM Approved

Description

Angle hose valves feature all brass* construction with forged or cast bodies for rigidity and light weight. Typical uses are in rack assemblies or any other application which requires a listed fire hose valve. Available in rough brass or polished chrome finish with a red hand wheel. **UL, ULC and FM Approved. Rated 300psi**



Installation

Install in accordance with customary installation practices. Use an approved thread sealant such as PipeFit Thread Sealing Paste with PTFE on the male threads to which the valve is being installed.

DO NOT OVER TIGHTEN. Over tightening of the valve during installation to the male pipe threads may crack or deform the valve body. Only use tools suitable for the installation of this product. Do not use pipe wrench extenders to increase leverage on pipe wrenches. This may result in valve damage as well as personal injury.

Specifications


Material:
Cast or Forged Brass* Body

Finish:
Rough Brass
Polished Chrome*

Threads:
2½" FNPT x FNPT
FNPT x MNST*
MBCT
MQST
MONT
MPHX
MTEM
MCLV
2½" GRV x FNPT
GRV x MNST
1½" FNPT x FNPT
FNPT x MNST

Friction loss is less than 3 psi thru an equivalent length of pipe per UL Standards.

*Contains lead. Not for use in water systems intended for human consumption.



3198 LIONSHEAD AVE
CARLSBAD, CA 92010
TEL + 1 760 599-1168
+ 1 800 344-1822
FAX + 1 800 344-3775

© 2012 Fire Protection Products, Inc.



WWW.FPPI.COM